

**SDS Report** Page 1 of 1 No. SHAEC1901441302 Date: Feb. 15, 2019

Jiangsu Highstar Battery Manufacturing Co.,Ltd No.306 Heping Road(s), Qidong City, Jiangsu, China

SGS Ref. No. SP19-002234-SH

Sample Name Lithium battery ISR18650 3.7V 1500mAh **End Uses** Power tool ,household appliance, etc

Composition/Ingredient of sample (as per client

submission)

report

Job Receiving Date Jan 21, 2019 Last Information Date Jan 22, 2019

SDS Preparation Period Jan 21 - Jan 28, 2019

Service Requested Preparation of Safety Data Sheet (SDS) for the sample with

submitted information.

Summary As per request, the contents and formats of the SDS are prepared

in accordance with US Regulations Relating to Labor 29 CFR

See section 3 Composition/information on ingredients on the SDS

1910.1200, and is provided per attached.

Remark:

This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated

for client's reference only.

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

Wei WANG, Terry Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.ags.com/en/Terms-and-Conditions.aspx">http://www.ags.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to the order of the conditions of the co

**Printing date 02/15/2019** 

Version number 1

Reviewed on 01/23/2019

## 1 Identification

- · Product identifier
- · Trade name: Lithium battery ISR18650 3.7V 1500mAh
- · Recommended use of the chemical and restrictions on use
- · Application of the substance / the preparation: Power tool, household appliance, etc
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Jiangsu Highstar Battery Manufacturing Co.,Ltd

No.306 Heping Road(s), Qidong City, Jiangsu, China

Tel: 13405720649

E-mail: lukz@highstar.com

- · Other US contact point: Not available
- · Further information obtainable from: Jiangsu Highstar Battery Manufacturing Co., Ltd
- · Emergency telephone number:

Lukaizuan

Tel: 13405720649

USA

Poison Center

Tel: + 1 800 222 1222

- · Reference Number: SP19-002234-SH; SHAEC1901441302
- . Remark

This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

## 2 Hazard(s) identification

· Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200)



GHS06 Skull and crossbones

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.

STOT RE 1 H372 Causes damage to the lung, the bone tissue and through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of OSHA Hazard Communication Standard (29 CFR 1910.1200).

(Contd. on page 2)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 1)

### · Classification system:

The classification is according to the latest edition of OSHA Hazard Communication Standard (29 CFR 1910.1200), and extended by company and literature data.

- · Label elements
- · Labelling according to OSHA Hazard Communication Standard (29 CFR 1910.1200)
- · Hazard pictograms







GHS05 GHS06 GHS08

## · Signal word Danger

### · Hazard-determining components of labeling:

Cobalt lithium manganese nickel oxide Lithium hexafluorophosphate(1-)

### · Hazard statements

H330 Fatal if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer. Route of exposure: Inhalation.

H372 Causes damage to the lung, the bone tissue and through prolonged or repeated exposure. Route of exposure: Inhalation.

#### · Precautionary statements

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

*P264* Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

*P308+P313 IF exposed or concerned: Get medical advice/attention.* 

P320 Specific treatment is urgent (see on this label).
P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Hazards not otherwise classified (HNOC) No further relevant information available.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture of the substances listed below with nonhazardous additions.

For the wording of the listed hazard statements refer to Section 16.

(Contd. on page 3)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

		(Contd. of page 2)
· Composition:		
	Cobalt lithium manganese nickel oxide	32.0%
	🔗 Acute Tox. 2, H330; & Carc. 1A, H350; STOT RE 1, H372	
7439-89-6	iron	23.0%
7440-50-8	copper	16.0%
7782-42-5	Graphite	15.0%
7429-90-5	Aluminum	8.0%
9003-07-0	polypropylene	3.0%
21324-40-3	Lithium hexafluorophosphate(1-)	3.0%
	📀 Acute Tox. 3, H301; 🗞 STOT RE 1, H372; 📀 Skin Corr. 1A, H314	

# 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth with water.

Never give anything by mouth to an unconscious person.

Call a doctor immediately.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

- · Special protective equipment and precautions for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

Avoid contact with eyes.

Avoid formation of dust.

Ensure adequate ventilation.

Keep away from ignition sources.

(Contd. on page 4)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 3)

Use respiratory protective device against the effects of fumes/dust/aerosol.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Use neutralizing agent.

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

## 7 Handling and storage

## · Precautions for safe handling:

Avoid contact with eyes.

Keep away from heat and direct sunlight.

Prevent formation of dust.

Prevent short cut and movement which could lead to short circuits.

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

For the general occupational hygienic measures refer to Section 8.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

## 8 Exposure controls/personal protection

## 7440-50-8 copper (16.0%)

PEL (USA)	Long-term value: $1*0.1**mg/m^3$
	as Cu *dusts and mists **fume
REL (USA)	Long-term value: $1*0.1**mg/m^3$
	Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0.2** mg/m³

# 7782-42-5 Graphite (15.0%)

PEL(USA)	Long-term	value:	15	mppcf*	mg/m³
----------	-----------	--------	----	--------	-------

\*dusts and mists; \*\*fume; as Cu

\*impinger samples counted by light field techn.

REL (USA) Long-term value: 2.5\* mg/m³

\*respirable dust

TLV (USA) Long-term value: 2\* mg/m³

all forms except graphite fibers; \*resp. fraction

(Contd. on page 5)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 4)

#### 7429-90-5 Aluminum (8.0%)

PEL (USA) Long-term value: 15\*; 5\*\* mg/m<sup>3</sup>

\*Total dust; \*\* Respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

as Al\*Total dust\*\*Respirable/pyro powd./welding f.

TLV (USA) Long-term value: 1\* mg/m³ as Al; \*as respirable fraction

#### · Regulatory information

PEL (USA): Guide to Occupational Exposure Values (OSHA PELs) REL (USA): Guide to Occupational Exposure Values (NIOSH RELs) TLV (USA): Guide to Occupational Exposure Values (ACGIH)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Based on the composition shown in Section 3, the following measures are suggested for occupational safety measure

#### · Appropriate engineering controls:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

See Section 7 for information about design of technical facilities.

#### · Personal protective equipment

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · General Information
- · Appearance:

Form: Solid

(Contd. on page 6)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

	(Contd. of pa
Color:	Blue
Odor:	Odorless
Odor threshold:	Not available.
pH-value:	Not available.
Change in condition	
Melting point/freezing point:	Not available.
Boiling point / Boiling range:	Not available.
Flash point:	Not available.
Flammability (solid, gaseous):	Not available.
Auto-Ignition temperature:	Not available.
Decomposition temperature:	Not available.
Explosion limits:	
Lower:	Not available.
Upper:	Not available.
Vapor pressure:	Not available.
Density:	Not available.
Relative density	Not available.
Vapor density	Not available.
Evaporation rate	Not available.
Solubility in / Miscibility with	
Water:	Not available.
Partition coefficient (n-octonol/wat	er): Not available.
Viscosity:	
Dynamic:	Not available.
Kinematic:	Not available.
Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No decomposition if used according to specifications.
- · Chemical stability Stable under recommended storage conditions.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Acute toxicity
- · LD/LC50 values that are relevant for classification:

7439-89-6 iron

Oral LD50 30,000 mg/kg (rat)

- · Primary irritant effect
- $\cdot$  Skin corrosion/irritation: Irritant to skin and mucous membranes.
- · Serious eye damage/irritation: Strong irritant with the danger of severe eye injury.
- · Respiratory or skin sensitisation: Sensitization possible.

(Contd. on page 7)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 6)

### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

*Irritant* 

Carcinogenic.

Corrosive

Harmful

Very toxic

· Carcinogenic categories

· Carcinogenic	cutegories	
· IARC (Intern	national Agency for Research on Cancer)	
182442-95-1	Cobalt lithium manganese nickel oxide	1
9003-07-0	polypropylene	3
· NTP (Nation	al Toxicology Program)	
182442-95-1	Cobalt lithium manganese nickel oxide	K
· OSHA-Ca (C	Occupational Safety & Health Administration)	
None of the i	ngredients is listed.	

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN3480	
· UN proper shipping name		
$\cdot DOT$	Lithium ion batteries	
· IMDG, IATA	LITHIUM ION BATTERIES	

USA ·

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 7) · Transport hazard class(es) · DOT, IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles · Label · Packing group · DOT, IMDG, IATA · Environmental hazards Not applicable. · Special precautions for user Warning: Miscellaneous dangerous substances and articles · EMS Number: F-A,S-I· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · IMDG · Limited quantities (LQ) Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity Referring to the Certification for Safe Transport of Chemical · Remarks: Goods (Report No. 2119374724) issued by Shanghai Research Institute of Chemical Industry Testing Co., Ltd, LI-ION BATTERY ISR18650 3.7V 1500mAh (Sample Model: ISR18650) is tested and is passed in accordance with: special provision 188 of Regulation (upon supplier's information). Referring to the Certification for Safe Transport of Chemical Goods (Report No. 2119374724) issued by Shanghai Research Institute of Chemical Industry Testing Co., Ltd, Inspection method and procedure of LI-ION BATTERY ISR18650 3.7V 1500mAh (Sample Model: ISR18650) is IMO International Maritime Dangerous Goods Code (2016 Edition) (upon supplier's information).  $\cdot$  IATA Referring to the Certification for Safe Transport of Chemical · Remarks: Goods (Report No. 2119374713) issued by Shanghai Research Institute of Chemical Industry Testing Co., Ltd, Inspection method and procedure of LI-ION BATTERY ISR18650 3.7V 1500mAh (Sample Model: 18650) is IATA Dangerous Goods Regulations (DGR) 60th Edition (upon supplier's information). UN 3480 LITHIUM ION BATTERIES · UN "Model Regulation":

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 9)

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

		Contd. of pag
Section 313 (Specific toxic ch		
182442-95-1 Cobalt lithium r	ianganese nickel oxide	
7440-50-8 copper		
7429-90-5 Aluminum		
TSCA (Toxic Substances Con	trol Act):	
All ingredients are listed.		
Proposition 65		
Chemicals known to cause ca	ncer:	
182442-95-1 Cobalt lithium r	ıanganese nickel oxide	
Chemicals known to cause re	productive toxicity for females:	
None of the ingredients is liste	d.	
Chemicals known to cause re	productive toxicity for males:	
None of the ingredients is liste	• •	
Chemicals known to cause de	velopmental toxicity:	
None of the ingredients is liste	d.	
New Jersey Right-to-Know Li	st:	
7440-50-8 copper		
7782-42-5 Graphite		
7429-90-5 Aluminum		
New Jersey Special Hazardoi	s Substance List:	
7429-90-5 Aluminum		F3, F
Pennsylvania Right-to-Know	List:	
7440-50-8 copper		
7782-42-5 <i>Graphite</i>		
7429-90-5 Aluminum		
Pennsylvania Special Hazard	ous Substance List:	
7440-50-8 copper		
7429-90-5 Aluminum		
Cancerogenity categories		
EPA (Environmental Protects	on Agency):	
7440-50-8 copper		
TLV (Threshold Limit Value	established by ACGIH):	
7429-90-5 Aluminum	·	A

# 16 Other information

· Relevant hazard statements

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H330 Fatal if inhaled.

H350 May cause cancer. Route of exposure: Inhalation.

H372 Causes damage to the lung, the bone tissue and through prolonged or repeated exposure. Route of exposure: Inhalation.

The contents and format of this SDS are in accordance with 29 CFR 1910.1200.

### DISCLAIMER OF LIABILITY:

The information in this SDS was obtained from sources which we believe are reliable. However, the

Printing date 02/15/2019 Version number 1 Reviewed on 01/23/2019

Trade name: Lithium battery ISR18650 3.7V 1500mAh

(Contd. of page 9)

information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

#### · Remark

This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

· Date of preparation / last revision 02/15/2019 / -

#### · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$ 

 $ACGIH: American\ Conference\ of\ Governmental\ Industrial\ Hygienists$ 

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Carc. 1A: Carcinogenicity - Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

End of document

USA