Product datasheet Characteristics

GGBL5000S

Lisse - Fuse connection unit - 1 gang - 13 A - white moulded





Main

Range	Lisse	
Aesthetic name	White moulded	
Product or component type	Fuse connection unit	
Device presentation	Complete product	
Colour tint	White moulded	
Quantity per set	Set of 1	

Complementary

Pilot light	Without LED	
Number of gangs	1 gang	
Material	Urea (carbamide)	<u>_</u>
Device mounting	Wall mounted	
Fixing mode	By screws	
Rated current	13 A, 250 V AC	
Connections - terminals	Screw terminals	<u>.</u>
Type of packing	Bag	
Width	87 mm	<u> </u>
Height	87 mm	<u> </u>
Depth	25 mm	
Product weight	0.091 kg	<u>a</u>
-		*

Environment

Standards	BS 1363
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	