

05422 tesamoll® Door-to-floor Foam Tape

Product Description/ Application:	tesamoll [®] door-to-floor- foam	 Self-adhesive, long- lasting foam profile
	The self-adhesive general purpose foam draught ex-	 Seals gaps from 1 to 19 mm
	cluder for doors is easy to apply on the bottom of every	Durability to 2 yearsSoft and flexible

door. Protects against cold,

saves energy. Recom-

mended for even floors.

Available in white and draughts, dust and noise and brown

- Best to be applied at 5°C-30°C
- Temperature-resistant . from -20°C to +40°C

tesa SE P.O. Box 57 02 62 D-22771 Hamburg Telephone +49-40-49 09 5593 +49-40-49 09 18 5593 Telefax

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.



tesa SE

Quality management

Internal page - Product information

Product name and -number: tesamoll® 05422 door-to-floor foam

Dimensions:

Colour	Lengths / widths / thickness of profiles	
White or brown	1m: 38mm: 2mm	

Technical Data: (mean values)

Backing: Backing tape:	PVC Non-woven	Adhesion/ Steel	≥ 2,5 N/cm
Total thickness (without re- lease liner):	2,32 +0,35/-0,25 mm	Gap coverage	1 – 19 mm
Adhesive:	Acrylate		

8320 - 02/08

 tesa SE

 P.O. Box 57 02 62

 D-22771 Hamburg

 Telephone
 +49-40-49 09 2618

 Telefax
 +49-40-49 09 4621

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.