

Equipment Wire

Order code	Manufacturer code	Description
01-2330	n/a	100M REEL RED/BLACK 16/0.2MM WIRE (RC)
01-2332	n/a	100M REEL RED/BROWN 16/0.2MM WIRE (RC)
01-2334	n/a	100M REEL RED/GREEN 16/0.2MM WIRE (RC)
01-2336	n/a	100M REEL RED/BLUE 16/0.2MM WIRE (RC)
01-2338	n/a	100M REEL ORANGE/BLACK 16/0.2MM WIRE
01-2340	n/a	100M REEL ORANGE/RED 16/0.2MM CABLE
01-2342	n/a	100M REEL YELLOW/BLACK 16/0.2MM CABLE RC
01-2344	n/a	100M REEL YELLOW/RED 16/0.2MM CABLE
01-2346	n/a	100M REEL YELLOW/GREEN 16/0.2MM CABLE
01-2348	n/a	100M REEL GREEN/RED 16/0.2MM CABLE
01-2350	n/a	100M REEL VIOLET/RED 16/0.2MM CABLE
01-2352	n/a	100M REEL GREY/BLACK 16/0.2MM CABLE (RC)
01-2354	n/a	100M REEL GREY/BLUE 16/0.2MM CABLE (RC)
01-2356	n/a	100M REEL WHITE/BLACK 16/0.2MM CABLE RC
01-2358	n/a	100M REEL WHITE/RED 16/0.2MM CABLE (RC)
01-2360	n/a	100M REEL PINK/BLACK 16/0.2MM CABLE RC
01-2362	n/a	100M REEL GREEN/YELLOW 16/0.2MM CABLE RC

Equipment Wire	Page 1 of 2
The enclosed information is believed to be correct, Information may change 'without notice' due to product improvement. Users should ensure that the product is suitable for their use. E. & O. E.	Revision A 04/07/2003

16/0.2mm Equipment Wire – (Bi-Colours)

Equipment Wires to Defence Standard 61-12 Part 6

Specification

16/0.2mm Type 2 [0.5mm²]

Conductor	:	16 Strands of 0.2mm diameter tinned annealed copper wire
Insulation	:	PVC to a radial thickness of 0.3mm
Diameter	:	1.55mm nominal OD
Rating	:	1KV r.m.s., 3.0 amps at 70°C 4.0 amps at 25°C ambient Maximum resistance at 20°C - 38 ohms/Km

NB:- Wires manufactured to Defence Standard 61-12 Part 6 types 1, 2 and 3 also comply with the requirements of BS 4808 classes 1, 2 and 3 for corresponding stranding and types. Because the requirements of Defence Standard 61-12 Part 6 are more rigorous than that required by BS 4808 the converse is not necessarily true.