

FICHA TÉCNICA / TECHNICAL INFORMATION

STARWELD

(ref. TEC-800)

CE CAT II



DESCRIPCIÓN

Pantalla de soldadura de diseño fabricada en nylon especial ultra flexible de alta resistencia al impacto y mínimo peso (347 grs.) con laterales y parte superior nervada, reforzando la estructura.

Adaptador a cabeza abatible y regulable mediante carraca con banda de sudoración multiperforada y recambiable.

Visor de oscurecimiento automático incorporado (98 x 44 mm) con doble sensor y controles internos de regulación manual del factor de oscurecimiento (de 9 a 13), sensibilidad, retardo (de 0.1 a 1 seg) y modo de trabajo (soldeo/amolado).

Clase óptica 1.

Protección UV/IR: Hasta DIN 16.

Estado claro: Grado de protección DIN 3,5.

Rango de Protección: Variable DIN 9 a 13.

Tiempo de conmutación: 0,06 ms.

Retardo: de 0,1 a 1 seg.

Temperatura de trabajo: de -10°C a +55°C.

Alimentación por célula solar y dos baterías AAA

APLICACIONES

Recomendada para soldadura MAG, MIG y TIG, corte por plasma y amolado. No Adecuada para soldadura láser o soldadura o corte con oxiacetileno.

ESPECIFICACIONES

Marcaje: EN 175 CE
Materiales: Nylon alta resistencia
Normativa: EN 175:1997

DESCRIPTION

Welding helmet with advanced design made of special ultra-flexible nylon with high impact strength and minimum weight (347 gr) with side and top nerves reinforcing the structure

Foldable and adjustable head adaptor with multiperforated and replaceable sweatband and wheel ratchet adjustment.

Built-in autodarkening visor (98x44 mm) with double sensor and internal shade (9 to 13), sensitivity, delay (0.1 to 1 sec) and working mode (welding/grinding) controls.

Optical Class 1.

UV/IR Protection: up to DIN 16

Light state of protection: shade DIN 3.5

Degree of protection: variable DIN 9 to 13.

Switch time of 0.06 msec.

Delay: from 0.1 to 1 seg

Operating temperature -10°C to +55°C.

Powered by solar cell and 2 AAA batteries.

APPLICATIONS

Recommended for MAG, MIG and TIG welding, plasma cut and grinding. Not suitable for laser welding or oxyacetylene Welding/Cutting.

SPECIFICATIONS

Marking: EN 175 CE
Materials: High-resistant nylon
Norms: EN 175:1997

Los productos tendrán larga vida de servicio cuando se usen siguiendo la información suministrada y su duración dependerá del tratamiento y aplicación de los productos. La protección no será la adecuada o total si los productos están dañados, se usan de manera incorrecta o en aplicaciones no recomendadas. 3L Internacional declina toda responsabilidad por el uso indebido de estos productos. En caso de duda consultar con nuestro servicio técnico.

The products will have long life service life time when used following the given information and its duration will depend on the treatment and application of the gloves. The protection will not be suitable or total if the gloves are damaged, are used in a wrong way or in not recommended applications. 3L Internacional declines all responsibility for the inappropriate use of these products. In case of hesitation contact with our technical department.

45069 FT
09/02/15



Empresa certificada
Nº SGI-1050365



Empresa certificada
Nº SGI-6010459

N.R.S. 39-04347/S