



Características

- Núcleo de 6 placas de acero laminado de 2mm.
- Núcleo de acero S355 carbonitrurado, endurecido.
- Alta resistencia a la intemperie.
- Protector del tambor/cañuto de acero carbonitrurado incrustado en el núcleo.
- Embellecedor giratorio de acero aleado cementado.
- Embellecedor con cono antimordaza.
- Doble contraplaca interior de 4+4 mm de espesor.
- Sujeción mediante 4 tornillos de acero endurecido CAL 8.8, M6. Para posición de roseta DIN (38 mm.) posición de roseta Española (26,2-5,1 mm.). Punta cónica anti-taladro. Longitudes 55, 60 y 65 mm.
- Anillos de compensación para ajuste ancho puerta-longitud bombillo.
- Acabados: plata, oro, negro e inox.
- Válido para cerraduras con cilindros Diamant

Features:

- Core of six welded 2 mm laminated steel plates.
- Anti-drilling Carbonitrided (hardened) S355 steel core.
- Outer and inner cylinder protector of carbonitrided steel.
- Outer and inner cylinder protector inlaid in the core (impossible to disassemble).
- Rotatory decorative shield made of alloyed carbonized steel.
- Decorative shield with anti-clamping device.
- Double interior counterplate of 4+4 mm width.
- Fastening with 4 steel screws CAL 8.8. For DIN rosette holes (38 mm.) and Spanish rosette holes (26,2-5,1 mm.). Anti-drill conic ending. Length of the screws 55, 60 and 65 mm.
- Compensation rings for the adjustment between the door width and the cylinder length.
- Finishes: silver coated, gold coated, inox and black.
- Suitable for locks fitted with Diamant

