

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

December 2012

PRODUCT DATA SHEET

Product	Ring Remover
Туре	A mixture of fine abrasives dispersed in special water based lubricating medium.
Intended Use	Removal of water and heat mark damage from a range of polished surfaces such as lacquers, varnishes and Rustins French Polish .
Special Features	Low odour. Will not destroy attractive patina that has been acquired due to ageing.
Preparation	The surface must be clean, smooth, dry and free from wax, dust and contaminants. SHAKE WELL BEFORE USE
Application	Pour the Ring Remover onto a lint free cloth and rub with pressure over the mark in the direction of the grain until the mark is removed. If the mark does not disappear apply more Ring Remover to the cloth and continue rubbing until the mark is removed. Buff with a clean cloth and then wax if required. For deeper marks the Ring remover can be applied with Rustins Fine Steel Wool (grade0000). For satin or matt finishes the same grade of steel wool may be used to matt the surface down after the Ring Remover has been used as it may produce a shiny surface.
Coats	N/A
Drying Time	N/A
Re-coating Time	N/A
Application Temp.	Ideally 15-25°C.
Coverage	Coverage 10-12sq.metres/litre per coat, depending on the absorbency of the surface.
Maintenance	Re-apply when necessary.
Compatibility	Compatible most polished surfaces such as lacquers, varnishes and Rustins French Polish.
Settlement	SHAKE WELL BEFORE USE.
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal conditions. Protect from frost.
Hazards	Non-flammable. Flash point: Nil. Avoid contact with eyes, skin and clothing. Wash hands after use and dry them. A Full Safety Data Sheet is available upon request or on www.rustins.co.uk
Clean-Up	Warm soapy water.
Sizes	125ml