

SEVENTH STAGE

Assembly instructions

Take the assembled enclosure and put it into the enclosure compartment. Mark on the walls, with an awl, the ten holes on the profiles (Fig. 7.1). **IMPORTANT:** The profile must be perfectly plumb (Fig. 7.2). **NOTICE:** Ensure that in the wall there are no power or telephone lines, water pipes or gas.

OTTAVA FASE

EIGHTH STAGE

Move the enclosure away from the wall and with a drill pierce the ten holes where the marks were drawn up (Fig. 8.1). Insert anchors into the holes (Fig. 8.2). **NOTICE:** Ensure that in the wall there are no power or telephone lines, water pipes or gas.

NINTH STAGE

Assembly instructions

Take the assembled shower enclosure and add it in the shower compartment. Secure the enclosure to the walls with screws, being careful not to use excessive force.

TENTH STAGE

Profiles Section

Assembly instructions

From inside the shower compartment, insert, interlocking, the attachment door profile in the left side profile. Exercise, top to bottom, the pressure needed to hear the insert click. Proceed, then, for the entire length of the side profile.

ELEVENTH STAGE

Profiles Section

From inside the shower compartment, insert, interlocking, the attachment door profile in the right side profile. Exercise, top to bottom, the pressure needed to hear the insert click. Proceed, then, for the entire length of the side profile.

DODICESIMA FASE

Profiles Section

From inside the shower compartment insert, interlocking, the last semitransparent component of the folding doors in the left attachment door profile, previously installed. Exercise, top to bottom, the pressure needed to hear the insert click. Proceed, then, for the entire length of the side profile.

THIRTEENTH STAGE

Profiles Section

Assembly instructions

From inside the shower compartment insert, interlocking, the last semitransparent component of the folding doors in the right attachment door profile, previously installed. Exercise, top to bottom, the pressure needed to hear the insert click. Proceed, then, for the entire length of the side profile.

FOURTEENTH STAGE

Instructions

To prevent fraying, if necessary, secure the rail profiles with the screws, as shown.

Assembly instructions

Apply silicone on the outside of the enclosure and let it dry for at least 24 hours. Lubricate the rail profiles using liquid soap or liquid cream, to facilitate doors sliding.