

# BUDERUS Logatrend VC-, VCM-, C-Plan Heizkörper-Wattleistungen in der Übersicht



Höhe mm	Länge mm	Typ 11 Bautiefe 63 mm	Typ 21 Bautiefe 67 mm	Typ 22 Bautiefe 103 mm	Typ 33 Bautiefe 158 mm	Höhe mm	Länge mm	Typ 11 Bautiefe 63 mm	Typ 21 Bautiefe 67 mm	Typ 22 Bautiefe 103 mm	Typ 33 Bautiefe 158 mm
Wärmeleistung in Watt bei 70/55/20 °C / 55/45/20 °C						Wärmeleistung in Watt bei 70/55/20 °C / 55/45/20 °C					
300	400	176/114	235/151	310/198	458/292	400	400	219/141	295/190	387/247	563/358
	500	220/142	294/189	388/248	572/366		500	273/176	369/237	484/309	703/448
	600	264/171	353/227	465/297	687/439		600	328/212	443/285	581/371	844/537
	700	308/199	412/265	543/347	801/512		700	382/247	517/332	677/433	984/627
	800	351/228	471/303	620/396	915/585		800	437/282	590/380	774/495	1125/716
	900	395/256	530/341	698/446	1030/658		900	492/318	664/427	871/557	1266/806
	1000	439/285	588/379	775/495	1144/731		1000	546/353	738/475	968/618	1406/896
	1200	527/342	706/454	930/594	1373/877		1200	656/423	885/570	1161/742	1688/1075
	1400	615/399	824/530	1085/693	1602/1024		1400	765/494	1033/665	1355/866	1969/1254
	1600	703/455	941/606	1240/792	1831/1170		1600	874/565	1181/760	1548/989	2250/1433
	1800	791/512	1059/681	1395/891	2060/1316		1800	984/635	1328/855	1742/1113	2531/1612
	2000	879/569	1177/757	1550/990	2289/1462		2000	1093/706	1476/950	1935/1237	2813/1791
	2300	1010/655	1353/871	1783/1139	2632/1682		2300	1257/811	1697/1092	2226/1422	3234/2060
	2600	1142/740	1530/984	2015/1288	2975/1901		2600	1421/917	1918/1234	2516/1608	3656/2328
3000	1318/854	1765/1136	2325/1486	3433/2194	3000	1639/1058	2214/1424	2903/1855	4219/2687		

# BUDERUS Logatrend VC-, VCM-, C-Plan Heizkörper-Wattleistungen in der Übersicht



Höhe mm	Länge mm	Typ 11 Bautiefe 63 mm	Typ 21 Bautiefe 67 mm	Typ 22 Bautiefe 103 mm	Typ 33 Bautiefe 158 mm	Höhe mm	Länge mm	Typ 11 Bautiefe 63 mm	Typ 21 Bautiefe 67 mm	Typ 22 Bautiefe 103 mm	Typ 33 Bautiefe 158 mm
Wärmeleistung in Watt bei 70/55/20 °C / 55/45/20 °C						Wärmeleistung in Watt bei 70/55/20 °C / 55/45/20 °C					
500	400	261/168	352/227	460/293	666/424	600	400	302/194	406/260	532/339	765/486
	500	326/210	440/283	575/366	832/530		500	377/243	507/325	666/424	957/607
	600	391/253	528/340	690/439	999/636		600	452/291	608/390	799/509	1148/728
	700	456/295	616/396	805/513	1165/742		700	528/340	710/455	932/593	1339/850
	800	521/337	704/453	920/586	1332/848		800	603/388	811/520	1065/678	1530/971
	900	587/379	792/510	1035/659	1498/954		900	679/437	913/585	1198/763	1722/1093
	1000	652/421	880/566	1150/732	1665/1060		1000	754/485	1014/650	1331/848	1913/1214
	1200	782/505	1056/680	1380/879	1997/1272		1200	905/582	1217/780	1597/1017	2296/1457
	1400	913/589	1232/793	1610/1025	2330/1484		1400	1056/679	1420/910	1863/1187	2678/1700
	1600	1043/673	1408/906	1840/1172	2663/1696		1600	1206/776	1622/1040	2130/1356	3061/1942
	1800	1173/758	1585/1020	2070/1318	2996/1908		1800	1357/873	1825/1170	2396/1526	3443/2185
	2000	1304/842	1761/1133	2300/1464	3329/2120		2000	1508/970	2028/1300	2662/1695	3826/2428
	2300	1499/968	2025/1303	2645/1684	3829/2438		2300	1734/1116	2332/1496	3061/1949	4400/2792
	2600	1695/1094	2289/1473	2990/1904	4328/2756		2600	1960/1261	2636/1691	3461/2204	4974/3156
3000	1955/1263	2641/1699	3450/2197	4994/3180	3000	2262/1455	3042/1951	3993/2543	5739/3642		

# BUDERUS Logatrend VC-, VCM-, C Plan-Heizkörper-Wattleistungen in der Übersicht

Höhe mm	Länge mm	Typ 11 Bautiefe 63 mm	Typ 21 Bautiefe 67 mm	Typ 22 Bautiefe 103 mm	Typ 33 Bautiefe 158 mm
		Wärmeleistung in Watt bei 70/55/20 °C / 55/45/20 °C			
900	400	425/271	559/356	742/468	1068/673
	500	532/339	699/445	928/585	1335/841
	600	638/406	839/534	1113/701	1602/1010
	700	744/474	979/623	1299/818	1869/1178
	800	851/542	1118/712	1484/935	2136/1346
	900	957/609	1258/801	1670/1052	2403/1515
	1000	1063/677	1398/890	1855/1169	2671/1683
	1200	1276/812	1678/1068	2226/1403	3205/2020
	1400	1488/948	1957/1246	2597/1637	3739/2356
	1600	1701/1083	2237/1424	2968/1870	4273/2693
	1800	1914/1219	2516/1602	3339/2104	4807/3029
	2000	2126/1354	2796/1780	3710/2338	5341/3366
	2300	2445/1557	3215/2048	4267/2689	6142/3871
2600	2764/1760	3635/2315	4823/3040	6943/4376	
3000	3189/2031	4194/2671	5565/3507	8012/5049	



inklusive folgendem Zubehör