

		<b>Key features</b>	
		<ul style="list-style-type: none"> <li>· Live view, recording&amp;playback up to 12 MP resolution</li> <li>· Up to 8 channel IP cameras can be connected with built-in PoE inputs</li> <li>· Advanced H.265+ Video Compression</li> <li>· Supports iPhone、 iPad、 Android mobile remote monitoring</li> <li>· Connectable to the third-party network cameras</li> <li>· HDMI Video output at up to 4K (4096 × 2160) resolution</li> <li>· Annke Vision for easy remote view</li> <li>· Support 4-ch Human and vehicle targets detection</li> </ul>	
<b>Model Number</b>		<b>N48PAW</b>	
<b>NVR</b>			
Video & Audio	Decoding Format	H.264+/H.264/H.265/H.265+	
	IP Video Input	8CH PoE	
	Video Output	HDMI up to 4K (4096 × 2160), VGA up to 1080p(1920 × 1080)	
	Audio Input/Output	1/1 RCA	
	Incoming/outgoing Bandwidth	80/80 Mbps	
	Max Recording Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)	
	Max Playback Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)	
	Max Playback Channel	8CH	
Max Playback Capacity	1-ch@12 MP(4096 X 3072) (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps)		
Hard Drive	HDD	1 SATA Interface	
	HDD Capacity	Up to 8 TB Capacity	
External Interface	Network Interface	1, RJ-45 10/100Mbps self-adaptive Ethernet interface	
	PoE	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface, IEEE 802.3 af/at	
	USB interface	USB 2.0*2	
Smart Function	Deep learning	8-ch Human and vehicle targets detection(Need IP camera support) 4-ch Human and vehicle targets detection(IP camera does not need to support this function but the resolution cannot exceed 4MP)	
	Smart Event	Line crossing detection, intrusion detection, region entrance detection, region exiting detection(Need IP camera support)	
General	Operating Power	DC 48 V	
	Power Consumption	≤10 W (Without HDD and PoE)	
		PoE: Max 25.5 W for Single Port	
	Working Temperature	14 °F ~ 131 °F/-10 °C ~+55 °C	
	Dimensions (W X H X D)	12.4" X 9.4" X 1.9"/315 X 240 X 48 mm	
Weight (Without Hard Disk)	2.2 lbs/1 kg		
<b>Packaging Contents</b>			
	NVR	1	
	USB Mouse	1	
	Power Adapter	1	
	1M network cable	1	
	1.8M HDMI cable	1	
	User's Manual For NVR	1	

		<b>Key features</b>	
		<ul style="list-style-type: none"> <li>· Live view, recording&amp;playback up to 12 MP resolution</li> <li>· Up to 16 channel IP cameras can be connected with built-in PoE inputs</li> <li>· Advanced H.265+ Video Compression</li> <li>· Supports iPhone、 iPad、 Android mobile remote monitoring</li> <li>· Connectable to the third-party network cameras</li> <li>· HDMI Video output at up to 4K (3840 × 2160) resolution</li> <li>· 2 SATA interfaces connectable for recording and backup</li> <li>· Annke Vision for easy remote view</li> <li>· Support 4-ch Human and vehicle targets detection</li> </ul>	
<b>Model Number</b>		<b>N46PCK</b>	
<b>NVR</b>			
Video & Audio	Video Compression	H.264+/H.264/H.265/H.265+	
	IP Video Input	16CH PoE	
	Video Output	HDMI up to 4K, VGA up to 1080p	
	Audio Input/Output	1/1 RCA	
	Incoming/Outgoing Bandwidth	160/80 M	
	Max. Recording Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)	
	Max. Playback Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)	
	Max. Playback Channel	16CH	
Hard Drive	HDD	2 SATA Interface	
	HDD Capacity	Up to 8 TB Capacity for each disk	
External Interface	Network Interface	RJ45 X1 (10/100/1000 M)	
	PoE	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface, IEEE 802.3 af/at	
	USB	2X USB 2.0	
Smart Function	Deep learning	16-ch Human and vehicle targets detection(Need IP camera support)	
		4-ch Human and vehicle targets detection(IP camera does not need to support this function but the resolution cannot exceed 4MP)	
	Smart Event	Line crossing detection, intrusion detection, region entrance detection, region exiting detection(Need IP camera support)	
General	Operating Power	AC 100-240 V	
	Power Consumption	≤15 W (Without HDD and PoE)	
		PoE: Max. 25.5W for Single Port	
	Working Temperature	14 °F — 131 °F/-10 °C — 55 °C	
	Dimensions (W X H X D)	15.2" X 12.4" X 2.0"/385 X 315 X 52 mm	
Weight (Without Hard Disk)	6.6 lbs./3 kg		
<b>Packaging Contents</b>			
	NVR	1	
	USB Mouse	1	
	Power Cable	1	
	1M network cable	1	
	1.8M HDMI cable	1	
	User's Manual For NVR	1	

		<b>Key features</b>	
		12 MP Recording Resolution 32 IP Camera Inputs (256 Mbps Total Inbound Bandwidth) H.265+/H.265/H.264+/H.264/MPEG4 4K (3840 × 2160) HDMI Video Output Independent HDMI and VGA Outputs 4 × SATA HDD Interfaces Smart Search and Smart Playback Alarm and Audio I/O Long Distance (100 to 300 m) Network Transmission via PoE	
<b>Model Number</b>		<b>N931BB</b>	
<b>NVR</b>			
Video & Audio	Video Compression	H.265+/H.265/H.264+/H.264/MPEG4	
	IP Video Input	32 Channel (Include 16 Channel PoE)	
	Video Output	HDMI up to 4K, VGA up to 1080p, CVBS	
	Audio Input/Output	1/1 RCA	
	Incoming/outgoing Bandwidth	256 Mbps	
	Max Recording Resolution	Up to 12MP	
	Max Playback Resolution	Up to 12MP	
	Max Playback Channel	16 Channel	
Max Playback Capacity	2CH @12MP (20 fps)/4CH @8MP (25 fps)8-ch @ 4MP (30 fps)/16-ch @ 1080p (30 fps)		
ONVIF Protocol	Support		
Hard Drive	HDD	4 SATA Interface	
	HDD Capacity	Up to 12 TB Capacity for Each HDD(48 TB total)	
External Interface	Network Interface	RJ45 X1 (10/100/1000 M)	
	PoE	16 Ports (IEEE802.3at/af)	
	Alarm Input/Output	16/4	
	Serial Interface	1 RS-485 (Half-Duplex), 1 RS-232	
	USB	Front Panel: 2X USB 2.0; Rear Panel: 1X USB 3.0	
General	Operating Power	100-240V	
	Power Consumption	<20 W (Without HDD and PoE)	
	Working Temperature	14 °F — 131 °F/-10 °C — +55 °C	
	Dimensions (W X H X D)	17.5" X 15.7" X 2.8" (445 mm X 400 mm X 71 mm)	
Weight (Without Hard Disk)	≤ 11 lbs. (5 kg)		
<b>Packaging Contents</b>			
	NVR	1	
	USB Mouse	1	
	Remote Control	1	
	Power Adapter	1	
	1 m Network cable	1	
	1.8 m HDMI cable	1	
	User Manual For NVR	1	

		<b>Key features</b>	
		<ul style="list-style-type: none"> <li>· Up to 64-ch IP cameras can be connected (up to 12 MP)</li> <li>· Connectable to the third-party network cameras</li> <li>· Up to 2-ch@32MP/8-ch@8MP decoding capacity</li> <li>· H.265+ compression effectively reduces the storage space by up to 75%</li> <li>· HDMI1/VGA1 and HDMI2/VGA2 outputs provided</li> <li>· HDMI1 Video output at up to 8K or 4K resolution</li> <li>· Up to 8 SATA interfaces and 1 eSATA interface for HDD connection, and 14TB capacity for each HDD</li> <li>· Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth</li> <li>· Supports special cameras, including people counting camera, ANPR (automatic number plate recognition) camera, and fisheye camera</li> <li>· Advanced streaming technology enables smooth live view in poor network conditions</li> <li>· 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces</li> <li>· Supports RAID 0, 1, 5, 6, 10 and N+M hot spare for even more reliable data storage.</li> </ul>	
<b>Model Number</b>		<b>N951BC</b>	
<b>NVR</b>			
Video & Audio	Decoding Format	H.264+/H.264/H.265/H.265+	
	IP Video Input	64-ch	
	Video Output	HDMI 1 up to 8K, HDMI 2 up to 4K, VGA 1 & VGA 2 up to 1080p, CVBS	
	Audio Input/Output	2/1 RCA	
	Incoming & Outgoing Bandwidth	400/400Mbps	
	Recording Resolution	32 MP/24 MP/12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3MP/1080p	
	Synchronous Playback	16-CH	
	Decoding Capability	2-ch@32 MP (30 fps)/8-ch@8 MP (30 fps)/16-ch@4 MP (30 fps)/32-ch@1080p (30 fps)	
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2/PCM	
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS		
Hard Drive	HDD	8 SATA Interface, 1 eSATA interface	
	HDD Capacity	Up to 14 TB Capacity for Each HDD	
	RAID Type	RAID0, RAID1, RAID5, RAID6, RAID10	
External Interface	Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	
	Serial Interface	1 RS-485 (full-duplex), 1 RS-232	
	Alarm Input/Output	16/9	
	Power output	Ctrl 12V 1A& DC 12V 1A	
	USB	Front panel: 2 × USB 2.0; Rear panel: 2 × USB 3.0	
General	Operating Power	100 to 240 VAC, 50 to 60 Hz	
	Max. Power	200 W	
	Power Consumption	≤ 50 W (without HDD)	
	Chassis	2U chassis	
	Working Temperature	14 °F ~ 131 °F/-10 °C ~+55 °C	
	Dimensions (W X H X D)	445 × 465 × 93 mm ( 17.5"× 18.3" × 3.7")	
Weight (Without Hard Disk)	≤ 10 kg (22 lb)		
<b>Packaging Contents</b>			
	NVR	1	
	USB Mouse	1	
	Power Adapter	1	
	1M network cable	1	
	1.8M HDMI cable	1	
	User's Manual For NVR	1	