

Made in CHINA by / Fabriqué en CHINE par / Hergestellt in CHINA von /
Gemaakt in CHINA door / Fabricado en CHINA por / Prodotto in CINA da /
Fabricado na CHINA por / Vyrobené v ČINE od / Vyrobené v ČINE od /
Wyprodukowane w CHINACH przez: **Varan Motors**



Imported by / Importé par / Importiert durch / Geïmporteerd door / Importado
por / Importato da / Importado por / Importované spoločnosťou / Dovezeno
spoločnosť / Importowane przez:

BCIE SARL
15 rue de Mensdorf,
L-5380 Uebersyren,
Luxembourg,
+352/26908036



"© 2024 BCIE SARL. All rights reserved."
"© 2024 BCIE SARL. Tous droits réservés."
"© 2024 BCIE SARL. Alle Rechte vorbehalten."
"© 2024 BCIE SARL. Alle rechten voorbehouden."
"© 2024 BCIE SARL. Todos los derechos reservados."
"© 2024 BCIE SARL. Tutti i diritti riservati."
"© 2024 BCIE SARL. Todos os direitos reservados."
"© 2024 BCIE SARL. Všetky práva vyhradené."
"© 2024 BCIE SARL. Všechna práva vyhrazena."
"© 2024 BCIE SARL. Wszelkie prawa zastrzeżone."

DIESEL TRANSFER PUMP



Summary

CYB with DC12V is a small sized high efficiency designed oil pump with big flowrate, high delivery head, vehicle battery driven and can be easily operated.

It can work with high ignition point oil such as diesel, machine oil and transformer oil, etc. (Forbidden to work with combustible oil such as gasoline etc.), suitable for small gas stations and self-filling and repairing for mobile machinery shops and etc.

Features

1. Big flowrate and strong suction.
2. Vehicle battery driven, easy and quick.
3. Firm and stable

Technical Parameter

Model	Power	Voltage	Inlet/Outlet	Max.flow	Max.sucking height	Max.delivery height	Speed
CYB150	160W	12V/24V DC	3/4" (1")	40L/min	5m	10m	3600r/min

Product Performance & Applications

FT with DC12V has passed strict test for temperature resistance and aseismic capability, the protection level IP55, built-in by-pass protective valve, it can be widely used in machineries and watercrafts, make refuelling more easier in the open.

Notice

1. Voltage supply must be confirmed before connecting cable.
2. Power supply: 12V DC, $\pm 5\%$.
3. A small quantity of liquid must be added to prime the pump before using for first time. Connect the input and output pipes according to the arrow symbol on the pump.
4. All the pumps and connectors must be well sealed and no air leakage.
To make sure the cleanness of the oil, please use the bottom valve with filter gauze we provide.
Time: 20mins maximum use for each continuous run.