Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or	trade mark:	Meykoers
------------	---------	-------------	----------

Supplier's address: Apex CE Specialists GmbH, Ravolzhauser str. 3la63543Neuberg, DE

Model identifier: LM2835-WC120-WW

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

			T	
Lighting technology used:	LED	Non-directional or	NDLS	
		directional:		
Light source cap-type	Lead wire			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light	No	
		source (CLS):		
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
_ ·	nption in on- 00 h), rounded st integer	6	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	580 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		5,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	50	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image	
sions without	Width	8		in last page	
separate con- trol gear, light- ing control	Depth	1			

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,448
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value	6	Survival factor	1,00
the lumen maintenance factor	0,98		

(a)'-': not applicable; (b)'-': not applicable;

