



Vaso autoclave con membrana intercambiabile per circuiti di acqua sanitaria.  
 Pressure tank with replaceable membrane for pressurized systems of sanitary water.  
 Réservoir sous pression à vessie remplaçable pour systèmes d'eau sanitaire.  
 Vertikales Druckausdehnungsgefäß mit austauschbarer Membrane für Trinkwassersysteme.  
 Acumulador hidroneumático con membrana recambiable para circuitos de agua sanitaria.

Temperatura d'esercizio  
 Working temperature  
 Température d'exercice  
 Betriebstemperatur  
 Temperatura de trabajo

- 10° C  
 + 100° C

Colore della verniciatura esterna  
 External finish color  
 Couleur de la peinture externe  
 Externe Beendenfarbe  
 Color pintura exterior

**RAL 5015**

Membrana in gomma  
 Rubber membrane  
 Vessie en gomme  
 Gummimembrane  
 Membrana en goma

**EPDM**

Controflangia zincata - Counter flange galvanized  
 Contre-bride galvanisé - Gegenflansch verzinkt - Contra brida galvanizada



Garanzia sul prodotto mesi: - Warranty months:  
 Garantie mois: - Monate Garantie: - Garantía meses:

**24**

Modello Model Modèle Model Modelo	Codice Code Code Code Código	Altezza Height Hauteur Höhe Altura H (mm)	Diametro Diameter Diamètre Durchmesser Diámetro Ø (mm)	Lunghezza Length Longeur Länge Longitud L (mm)	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck Presión máxima de trabajo (bar)	Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck Presión de precarga estándar (bar)	Imballo Packing Emballage Verpackung Embalaje (mm)	Attacco Connection Raccordement Anschluss Conexión (inch)
<b>VA018</b>	AAGOE11B01CC1	305	280	430	10	1,5	(Pz4) 520X580X610	1"
<b>VA024</b>	AAIOE11B01EC1	305	280	485	10	1,5	(Pz4) 520X580X610	1"
<b>VA035</b>	AAJOE11B01EA1	376	365	440	10	1,5	(Pz1) 380X400X460	1"
<b>VA050</b>	AAKOE11B01EA1	380	365	585	10	1,5	(Pz1) 380X400X590	1"
<b>VA060</b>	AALOE11B01EA1	385	365	690	10	1,5	(Pz1) 380X400X700	1"
<b>VA080</b>	AAMOE11B01EA1	430	410	725	10	1,5	(Pz1) 430X450X735	1"
<b>VA0100</b>	AANOE11B11EA1	520	495	685	10	1,5	(Pz1) 510X540X700	1"
<b>VA0150</b>	AAPOE11B11EA1	585	550	820	10	1,5	(Pz1) 570X610X850	1"

Temperatura d'esercizio  
 Working temperature  
 Température d'exercice  
 Betriebstemperatur  
 Temperatura de trabajo

- 10° C  
 + 100° C

Colore della verniciatura esterna  
 External finish color  
 Couleur de la peinture externe  
 Externe Beendenfarbe  
 Color pintura exterior

**RAL 5015**

Membrana in gomma  
 Rubber membrane  
 Vessie en gomme  
 Gummimembrane  
 Membrana en goma

**EPDM**

Controflangia verniciata - Painted counter flange  
 Contre-bride peinte - Lackierter Gegenflansch - Contra brida pintada



Garanzia sul prodotto mesi: - Warranty months:  
 Garantie mois: - Monate Garantie: - Garantía meses:

**24**

<b>VA0200</b>	AAQOG21B11FA1	628	600	920	10	2	(Pz1) 620X630X1030	1 1/4"
<b>VA0300</b>	AASOG21B11FA1	680	650	1082	10	2	(Pz1) 680X700X1290	1 1/4"

**Controflangia inox AISI 304 disponibile su richiesta. - Stainless steel AISI 304 counter flange available on request.**  
**Contre bride inox AISI 304 disponible sur requête. - Inox Flansch AISI 304 auf Anfrage.**  
**Contra brida en acero inox AISI 304 bajo demanda.**