



3182 - PLUG-IN EQUAL/UNEQUAL COMPACT ELBOW PLASTIC TAILPI



maximum working pressure	20 bar 2 MPa 290 psi
working temperature	-20 to 80 °C -4 to 176 °F 253 to 353 °K
vacuum capability	755 mm Hg
body	TECHNICAL POLYMER
'O'-rings	NBR
gripping ring	STAINLESS STEEL

Part Nb	ØD1 (MM)	ØD2 (MM)	ØG (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	(kg)
	All	All	All	All	All	All	All	All
3182 04 00	4	4	8.5	23	6	15.5	14	.005
3182 04 06	4	6	10.5	26.5	7	17	16	.004
3182 06 00	6	6	10.5	26.5	7	17	16	.001
3182 06 04	6	4	10.5	24.5	7	15.5	16	.001
3182 06 08	6	8	13.5	33.5	8	21.5	23	.007
3182 08 00	8	8	13.5	33.5	8	21.5	23	.003
3182 08 10	8	10	16	39	10	24.5	26.5	.01
3182 10 00	10	10	16	39	10	24.5	26.5	.004
3182 10 12	10	12	19	44.5	10.5	27.5	31	.016
3182 12 00	12	12	19	45.5	10.5	27.5	31	.007