

Datasheet

RS Pro 2 Output Toroidal Transformer, 120VA, 2 x 12V ac

RS Stock No: **671-8996**



Product Details

RS Pro 2 output toroidal transformer is a small size and low weight with traditional stacked laminated transformers. It has both primary and secondary windings connected in series or parallel. This transformer has primary voltage rating of 115 V ac, 230 V ac, secondary voltage rating of 2 x 12 V ac and power rating of 120 VA. Toroidal transformer meets EN 61558, IEC 742, UL 506, UL 1411, UL 478 and CE certified.


Features and Benefits

- Low induced noise (hum)
- Low level of radiated magnetic field
- Flexible leadouts for ease of installation
- 100% electrical and flash testing

**Specifications:**

Diameter	96 mm
Dimensions	96 (dia.) x 48 mm
Height	48 mm
Maximum Operating Frequency	60 Hz
Minimum Operating Frequency	50 Hz
Number of Outputs	2
Power Rating	120 VA
Primary Voltage Rating	230 V ac
Secondary Current	5 A
Secondary Voltage Rating	2 x 12 V ac
Termination Type	Copper Conductor
Weight	1.37 kg
Construction	Open
Standards Met	UL 506, IEC 61558 Class II, EN 61558 Class II, VDE0570 Class II, RoHS Compliant

Open Style, with leads, 230V Primary, 120VA



RS Code No.	RS Part No.	Full Load Vsec [V]	Rated Current per Sec [A]	No Load Vsec [V]	DC resistance [Ohms] @ 25° C
671-8996	81546-P1S2	2x12	5.000	2 x 13.31	2 x 0.1324
671-8990	81547-P1S2	2x15	4.000	2 x 16.64	2 x 0.2057
671-9003	81548-P1S2	2x18	3.333	2 x 19.97	2 x 0.3039
671-9006	81549-P1S2	2x25	2.400	2 x 27.85	2 x 0.6000
671-9000	81550-P1S2	2x55	1.091	2 x 61.13	2 x 2.9489

Primary Winding

Input Voltage : 230V±10 % @ 50/60Hz
 DC Resistance @25°C = 16 Ohms (approx)
 Magnetising Current @ 230V = 105.0mA (approx)
 Magnetising Current @ 253V = 275.0mA (approx)

Losses

Iron Losses 6.0 Watts (approx)
 Copper Losses 18.90 Watts (approx)

Temperature Class

Winding Wire (Primary & Secondary). Class H (180° C)
 Insulation between input and output. Class B (130° C)
 Connection lead insulation. Class A (105° C)

Standards

Designed,manufactured and tested according to the requirements of:
 EN61558 Class II, Non-Short-Circuit Proof
 VDE0570 Class II
 IEC61558 Class II
 UL506

Physical Data

Approximation Dimension Diameter 96mm*
 Height 48mm
 * Measured away from leadout bulge, allow extra 4mm at leads
 Approximate weight 1.37 Kg

Terminations

Primary Solid Copper Conductors (Extension of winding wire)
 double Insulated over their entire length with PVC tubing
 150mm Long, with 10mm tinned ends.

Secondary Solid copper conductors (extension of winding wire)
 insulated over their entire length with PVC tubing
 150mm Long, with 10mm tinned ends.