

S - 1/2" inch 12-point sockets




IMAGE UNAVAILABLE

Standards:

ASME B107.1

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Available as rack set Ref S.40U (3/8" --> 21/32") and Ref S.41U (11/16" --> 1").
- Finish: bright chrome.

	A [mm]	A [in]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	12-Point [mm]	Weight [g]
S.1/2		1/2"	22.8	18.9	36.0	10.4	12.0	50.0
S.11/16		11/16"	22.6	24.6	36.0	13.0	12.0	65.0
S.13/16		13/16"	24.6	28.6	38.0	16.0	12.0	80.0
S.15/16		15/16"	28.7	32.7	38.0	16.5	12.0	115.0
S.19/32		19/32"	22.8	21.4	36.0	12.0	12.0	55.0
S.1P	1.0		28.3	34.7	38.0	16.5	12.0	120.0
S.1P1/16		11/16"	29.2	36.6	44.0	19.0	12.0	150.0
S.1P1/4	1.25		35.1	42.5	44.0	20.0	12.0	205.0
S.1P1/8	1.125		31.3	38.7	44.0	20.0	12.0	170.0
S.1P3/16	1.1875		33.0	40.4	44.0	20.0	12.0	180.0
S.21/32		21/32"	23.1	24.1	36.0	13.0	12.0	60.0
S.25/32		25/32"	25.9	27.9	36.0	14.0	12.0	80.0
S.3/4		3/4"	25.0	27.0	36.0	14.0	12.0	75.0
S.3/8		3/8"	22.8	14.7	36.0	7.8	12.0	50.0
S.31/32		31/32"	27.7	34.1	38.0	16.5	12.0	115.0
S.5/8		5/8"	21.6	22.6	36.0	12.0	12.0	60.0
S.7/16		7/16"	22.8	16.5	36.0	9.0	12.0	50.0
S.7/8		7/8"	26.4	30.4	38.0	16.5	12.0	90.0
S.9/16		9/16"	22.8	20.2	36.0	10.5	12.0	50.0