



VT-15300ST LED SOLAR STREETLIGHT 4000K 3.2V 75AH LiFe PO4 BRIDGELUX CHIP IP65



FEATURES

- Solar Powered streetlight - Zero electricity cost
- Designed with remote control and Lamp Post/Wall Mount 2IN1 installation
- Maximum Installation and Mounting Height 6-8 Meters
- Perfectly built for outdoor application with Ingress protection of IP65
- Includes Protruding Pole, Mounting Arm, Solar Panel, 1.5M Cable, Expansion Screws, Solar Panel Bracket, 1 Expansion Plate and Remote Control
- Suitable for Pathways, Garden, Patio and similar outdoor environment

TECHNICAL INFORMATION

Solar Panel:	70W
Color Temperature:	4000K
Model:	VT-15300ST
Lumens:	3500
Color for Web:	Day White
Dimension:	200x530mm
Working Time:	8-10 Hours
LED Chip Type:	SMD
Beam Angle:	120°
Battery Type:	Life PO4, 3.2V 75000mAh Battery
IP Rating:	IP65
Wire Length:	1.5m
Charging Time:	4-6 Hours

IP65
STANDARD

02
YEAR
WARRANTY

LISTING DETAILS

SKU:	10228
Model:	VT-15300ST
EAN:	3800170205987
Commodity Code:	94054110

PACKAGING

Gross Weight (Kgs):	11.7
Unit CBM:	0.096279
Dimension:	200x530mm

MASTER BOX PACKAGING

Box Qty:	1
Qty Per Pallet:	18
Length (Box) mm:	740
Width (Box) mm:	685
Height (Box) mm:	195